

HIGH DEFINITION DIGITAL RECEIVER AND RECORDER

SRT 5441



- **DVR Ready via USB or eSATA External Mass Storage Device**
- **Simultaneous Recording and Playback**
- **EPG with Easy One-Touch Recording**
- **Time Shift and Timer Recording**
- **LAN Port for Internet Connectivity**
- **Freeview Compliant**



STRONG

not just by name

www.strong-technologies.com





SRT 5441 SPECIFICATIONS



TUNER

Guard Internal Modes	: 1/32, 1/16, 1/8, 1/4 Active Symbol Duration	Signal Level	: -78.5 - -25dBm
FEC Mode Rates	: 1/2, 2/3, 3/4, 5/6, 7/8	Input Impedance:	: 75 ohm
Input Connector	: IEC 169-2, Female	Wave Form	: OFDM
Frequency Range	: 170-860MHz	Carrier Mode	: 2K & 8K
Demodulator	: COFDM 2K/8K-Carrier		
Channel Bandwidth	: 7/8MHz Switchable by Software		

MPEG TS A/V Decoder

Transport Stream Profile Level	: MPEG-2 ISO/IEC 13818-1 : MPEG-II MP@ML, MPEG-II MP@HL : MPEG-IV AVC/H.264 HP@L4.0	Audio Decoding	: MPEG/Musical Layer & Dolby Digital
Video Resolution	: 720 x 576i/p, 1280 x 720p & 1920 x 1080i Selectable	Audio Mode	: Stereo / Joint Stereo / Mono
Video Formats	: 4:3 Letterbox, 4:3 Pan & Scan, 16:9 Pillarbox & 16:9 Full Screen	Sampling Rate	: 32KHz, 44.1KHz & 48KHz
		Input Rate	: Max. 15 Mbit/s

A/V Input/Output

TV SCART Video Output	: CVBS & RGB, Audio Output L & R	Video Output	: RCA/Cinch
VCR SCART	: A/V Output: CVBS, L/R		: Component Output, Y, Pb, Pr
Digital A/V Output S/PDIF	: A/V Input CVBS, RGB, L/R : HDMI 1.2 (High Definition Multimedia Interface) : Optical Digital Audio Output	Audio L/R	: S-Video : RCA/Cinch

Data Input/Output

RS-232C	: Transfer Rate 115Kbps, 9 PIN D-Sub Type	eSATA	: External SATA Interface (7200 RPM Support Only)
USB	: 2.0 Host	LAN	: 10/100Mbps Ethernet

System Resources

Main Processor	: 32bit Super Scalar RISC CPU (266MHz)	DDR DRAM	: 64Mbyte x 2, 32MByte x 2
Flash ROM	: 16Mbyte	EEPROM	: 256Kbit

Power Supply


Input Voltage	: AC 100-250V~, 50/60Hz	Power Consumption:	: Max. 40 W
Type	: SMPS (Switching Mode Power Supply)	Protection	: Separate Internal Fuse

Physical Specifications

Size (W x D x H)	: 335 x 247 x 58.8 mm
Weight	: 2.3 Kg
Operating Temperature	: 0°C ~ +45°C
Storage Temperature	: -10°C ~ +70°C

E. & O. E.

DISTRIBUTED BY:



STRONG TECHNOLOGIES PTY LTD. - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA 3803, AUSTRALIA
PH: +61 3 8795-7990 FAX: +61 3 8795-7991

TECHNICAL SUPPORT: 1 800 820 030

STRONG & CO. (FAR EAST), LTD. - P. O. BOX 85, YOKOHAMA, KANAGAWA-KEN, JAPAN 231-91 - FAX: +81 45 651-1842

www.strong-technologies.com

salesau@strong-technologies.com