



SRT 4922D+

HDTV

- مطابق مع البث ذو ثلاثية الأبعاد
- دقة الفيديو 1080p+i / 720p / 576p+i
- تسجيل الفيديو الرقمي و عرض البرامج مع فارق زمني على وحدة تخزين خارجية USB 2.0
- منفذ يو اس بي 2.0 (عدد 4) لتشغيل محول Wi-Fi و 3G، ألعاب، MP3، MPEG، عرض JPEG و تحديث البرامج
- منفذ إيثرنت (RJ45) لتحديث البرامج



- سعة 10,000 قناة
- مطابق لنظام DVB-S2/S، MPEG-4/2 متوافق مع H.264
- مخرج رقمي للصوت و الصورة عالية الجودة HDMI
- مخرج UHF 21-69 معالج للصوت و الصورة
- مخرج دولبي ديجيتال
- شاشة سينما 4:3 ، شاشة كاملة 16:9
- مسح شامل متقدم
- مسح يدوي و آلي
- تغذية آلية 250/100 فولت 50/60 هرتز (اس ام بي اس)

جهاز استقبال و تسجيل رقمي عالي الوضوح

HIGH DEFINITION DIGITAL SATELLITE TELEVISION RECEIVER AND RECORDER



STRONG

www.strong-technologies.com



www.facebook.com/strongtechnologies



www.twitter.com/strongtechnologies



www.youtube.com/strongtechnologies

not just by name

STRONG SRT 4922D+ SPECIFICATIONS



TUNER

Input Connector	: F-type, IEC 169-24, Female	DiSeqC control	: 1.2 Compliant, USALS
Loop Through Connector	: F-type, IEC 169-24, Female	Demodulation	: QPSK, 8PSK, 16APSK & 32APSK
Frequency Range	: 950MHz - 2150MHz	Input symbol rate	: DVB-S: 2 ~ 45Ms/s
Input impedance	: 75 unbalanced		: DVB-S2: 10 ~ 30Msps (QPSK & 8PSK)
			: 6Msps (16APSK), 27Msps (32APSK)
Signal level	: -25 to -65dBm	FEC decode	: DVB-S: 1/2, 2/3, 3/4, 5/6 and 7/8
LNB power & Polarization	: 13/18V, Max. 400mA		: DVB-S2: 1/2, 3/5, 2/3, 3/4, 4/5,
			: 5/6, 8/9, 9/10 (QPSK).
22 KHz tone	: 22±2KHz, 0.6±0.2V		: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (8PSK)

MPEG TS A/V Decoder

Transport Stream	: MPEG-2 ISO/IEC 13818-1	Audio Decoding	: MPEG/Musical Layer & Dolby Digital
Profile Level	: MPEG-II MP@ML, MPEG-II MP@HL	Audio Mode	: Stereo / Joint Stereo / Mono
	: MPEG-IV AVC/H.264 HP@L4.0	Sampling Rate	: 32KHz, 44.1KHz & 48KHz
Video Resolution	: 720 x 576i/p, 1280 x 720p & 1920 x 1080i/p	Input Rate	: Up to 15Mbit/s
	Selectable		
Video Formats	: 4:3 Letterbox, 4:3 Pan & Scan, 16:9 Pillarbox		
	& 16:9 Full Screen		

A/V Input/Output

Video Output	: CVBS RCA/Cinch	Audio Output	: L/R RCA/Cinch
Digital A/V Output	: HDMI 1.2a (High Definition Multimedia Interface)	S/PDIF Output	: Electrical Digital Audio
RF OUT	: IEC Male	Aerial In	: IEC Female

Modulator Section

Output	: PALG/I/K	CH	: 21-69UHF (PLL Controlled)
--------	------------	----	-----------------------------

Data Input/Output

LAN	: 10/100Mbps Ethernet	USB	: 2.0 Host (1 @ Front & 3 @ Rear)
-----	-----------------------	-----	-----------------------------------

System Resources

Main Processor	: 32 bit Processor (550MHz, 850DMIPS)	Flash ROM	: 8Mbyte
DDR3	: 128Mbyte	EEPROM	: 256Kbit

Power Supply


Input Voltage	: AC 100-250V~, 50/60Hz	Power Consumption	: Max. 25W
Type	: SMPS (Switching Mode Power Supply)	Protection	: Separate Internal Fuse

Physical Specifications

Size (W x D x H)	: 250 x 195 x 50mm	Weight	: 1Kg
Operating Temperature	: 0°C - +45°C	Storage Temperature	: -10°C - +70°C

E. & O. E.

DISTRIBUTED BY:



STRONG & CO. (FAR EAST), LTD. - P. O. BOX 85, YOKOHAMA, KANAGAWA-KEN, JAPAN 231-91 - FAX: +81 45 651-1842

www.strong-technologies.com

sales@strong-technologies.com