



SRT 4922D+ **HDTV**

- 3D Broadcasts Compatible via HDMI
- Video Resolution: 1080i/p, 720p, 576i/p
- DVR-Ready via USB External Mass Data Storage Device
- Time Shift, Record & Playback
- USB 2.0 Hosts (4) for Wi-Fi Adaptor, Games, MPEG & MP3 Playback, JPEG Viewing and Firmware Updates
- Ethernet Port (RJ-45) for Software Updates



- Embedded CONAX CAS7
- 10,000 Programmable Channels
- DVB-S/S2, MPEG-2/4, H.264 Compliant
- HDMI Output
- UHF 21-69 RF Modulator Output
- Programmable Function Keys: F1~F4 & 0~9
- Dolby Digital Electrical Output
- 16:9 Full Screen, 4:3 Letterbox & Full Screen
- Advanced Blind Scan
- Auto & Manual Channel Search
- Auto Voltage (AC 100 - 250V~) SMPS





www.strong-technologies.com

HIGH DEFINITION DIGITAL SATELLITE TELEVISION RECEIVER AND RECORDER



not just by name



STRONG SRT 4922D+ SPECIFICATIONS



TUNER

Input Connector	: F-type, IEC 169-24, Female	DiSeqC control	: 1.2 Compliant, USALS
Loop Through Connector	: F-type, IEC 169-24, Female	Demodulation	: QPSK, 8PSK, 16APSK & 32APSK
Frequency Range	: 950MHz - 2150MHz	Input symbol rate	: DVB-S: 2 ~ 45Ms/s
Input impedance	: 75 unbalanced		: DVB-S2: 10 ~ 30Msps (QPSK & 8PSK)
			: 6Msps (16APSK), 27Msps (32APSK)
Signal level	: -25 to -65dBm	FEC decode	: DVB-S: 1/2, 2/3, 3/4, 5/6 and 7/8
LNB power & Polarization	: 13/18V, Max. 400mA		: DVB-S2: 1/2, 3/5, 2/3, 3/4, 4/5,
			: 5/6, 8/9, 9/10 (QPSK).
22 KHz tone	: 22±2KHz, 0.6±0.2V		: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (8PSK)

MPEG TS A/V Decoder

Transport Stream Profile Level	: MPEG-2 ISO/IEC 13818-1	Audio Decoding	: MPEG/Musical Layer & Dolby Digital
	: MPEG-II MP@ML, MPEG-II MP@HL	Audio Mode	: Stereo / Joint Stereo / Mono
	: MPEG-IV AVC/H.264 HP@L4.0	Sampling Rate	: 32KHz, 44.1KHz & 48KHz
Video Resolution	: 720 x 576i/p, 1280 x 720p & 1920 x 1080i/p	Input Rate	: Up to 15Mbit/s
	Selectable		
Video Formats	: 4:3 Letterbox, 4:3 Pan & Scan, 16:9 Pillarbox & 16:9 Full Screen		

A/V Input/Output

Video Output	: CVBS RCA/Cinch	Audio Output	: L/R RCA/Cinch
Digital A/V Output	: HDMI 1.2a (High Definition Multimedia Interface)	S/PDIF Output	: Electrical Digital Audio
RF OUT	: IEC Male	Aerial In	: IEC Female

Modulator Section

Output	: PALG/I/K	CH	: 21-69UHF (PLL Controlled)
--------	------------	----	-----------------------------

Data Input/Output

LAN	: 10/100Mbps Ethernet	USB	: 2.0 Host (1 @ Front & 3 @ Rear)
-----	-----------------------	-----	-----------------------------------

System Resources

Main Processor	: 32 bit Processor (550MHz, 850DMIPS)	Flash ROM	: 8Mbyte
DDR3	: 128Mbyte	EEPROM	: 256Kbit

Power Supply


Input Voltage	: AC 100-250V~, 50/60Hz	Power Consumption	: Max. 25W
Type	: SMPS (Switching Mode Power Supply)	Protection	: Separate Internal Fuse

Physical Specifications

Size (W x D x H)	: 250 x 195 x 50mm	Weight	: 1Kg
Operating Temperature	: 0°C - +45°C	Storage Temperature	: -10°C - +70°C

E. & O. E.

DISTRIBUTED BY:



STRONG & CO. (FAR EAST), LTD. - P. O. BOX 85, YOKOHAMA, KANAGAWA-KEN, JAPAN 231-91 - FAX: +81 45 651-1842

www.strong-technologies.com

sales@strong-technologies.com